



MMA and TIG inverter electrode welding machine, in direct current (DC) with scratch striking. Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, etc. Characteristics: high welding current stability in spite of mains voltage fluctuations * regulation of arc force and hot start according to the type of electrode In use * anti-stick device * thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator ($\pm 15\%$) protections. Complete with MMA welding accessories and aluminium carry case.



PROFESSIONAL



Norms:	LVD: EN 60974-1	LVD: EN 50445	EMC: EN 60974-10						
CODE	V _{ph}	A _{MIN} A _{MAX}	A _{MAX} 40°C	A _{60%} 40°C	V _o	A _{60%} I _{MAX}	P _{60%} MAX	P _{GEN}	η
	V50/60Hz	A	A EN60974-1	A EN60974-1	V	A		kW	n%
815954	230 1 ph	5 200 DC	200 35 % DC	150 DC	85 DC	24 41	4 7	10	83
ϕ	ϕ MIN MAX DC	IP	W _H L	kg	BAR CODE				
cosphi	mm		mm(L,V,H)	kg		pz/pallet			
0,7	1,6 4	IP23	375 505 190	15	800489772372 3	30			